

GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

<https://www.global-antenna.com>

Specification

1 SCOPE

This specification shall cover the characteristics of the dielectric antenna element with the type **GLS1204**

2 PART NO.


PART NUMBER	CUSTOMER PART NO	SPECIFICATION NO
GLS1204		

3 OUTLINE DRAWING AND DIMENSIONS

3.1 Appearance: No visible damage and dirt.

3.2 The products conform to the RoHS directive and national environment protection law.

3.3 Dimensions



4 ELECTRICAL SPECIFICATIONS

4.1 Performance Characteristics

Items	Content
Nominal frequency MHz	1575~1608 (GPS : 1575, GLONASS : 1592~1608)
Center frequency (without adhesive tape on 15×15 mm ground plane)	1589 ± 3
Return Loss at 1575 MHz max dB	-11
Return Loss at 1603.5 MHz max dB	-11
Polarization Model	RHCP
Impedance	50Ω
Frequency Temperature Coefficient	20ppm/deg. °C max

Email: info@global-antenna.com Tel: 86-371-58561629

Add: Room 1124,BLDG C,Chaoliumao,High-Tech Zone, Zhengzhou,China


GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

<https://www.global-antenna.com>

4.2 RATING

Items	Requirement
Operating temperature	-40℃～+85℃
Storage temperature	-40℃～+105℃

4.3 Impedance Characteristic




5 TEST

5.1 Test Conditions

Parts shall be measured under a condition (Temp.:20℃±15℃, Humidity : 65%±20% R.H.).

5.2 Test fixture



6 ENVIRONMENTAL TEST

Email: info@global-antenna.com Tel: 86-371-58561629

Add: Room 1124,BLDG C,Chaoliumao,High-Tech Zone, Zhengzhou,China

GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

<https://www.global-antenna.com>

No.	Item	Test Condition	Remark
6.1	Humidity Test	The device is subjected to 90%~95% relative humidity $60^{\circ}\text{C} \pm 3^{\circ}\text{C}$ for 96h~98h, then dry out at $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and less than 65% relative humidity for 2h~4h. After dry out the device shall satisfy the specification in table 1.	It shall fulfill the specifications in Table 1.
6.2	High Temperature Exposure	The device shall satisfy the specification in table 1 after leaving at 105°C for 96h~98h, provided it would be measured after 2h~4h leaving in $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and less than 65% relative humidity.	It shall fulfill the specifications in Table 1.
6.3	Low Temperature	The device shall satisfy the specification in table 1 after leaving at -40°C for 96h~98h, provided it would be measured after 2h~4h leaving in $25^{\circ}\text{C} \pm 5^{\circ}\text{C}$ and less than 65% relative humidity.	It shall fulfill the specifications in Table 1.
6.4	Temperature Cycle	Subject the device to -40°C for 30 min. followed by a high temperature of 105°C for 30 min cycling shall be repeated 5 times. At the room temperature for 1h prior to the measurement.	It shall fulfill the specifications in Table 1.
6.5	Vibration	Subject the device to vibration for 2h each in x, y and z axis with the amplitude of 1.5mm, the frequency shall be varied uniformly between the limits of 10Hz~55Hz.	It shall fulfill the specifications in Table 1.
6.6	Soldering Test	Lead terminals are heated up to $350^{\circ}\text{C} \pm 10^{\circ}\text{C}$ for $5\text{s} \pm 0.5\text{s}$ with brand iron and then element shall be measured after being placed in natural conditions for 1 h. No visible damage and it shall fulfill the specifications in Table 1	It shall fulfill the specifications in Table 1.
6.7	Solder ability	Lead terminals are immersed in soldering bath of $260^{\circ}\text{C} \sim 290^{\circ}\text{C}$ for $3\text{s} \pm 0.5\text{s}$. More than 95% of the terminal surface of the device shall be covered with fresh solder.	The terminals shall be at least 95% covered by solder.
6.8	Terminal Pressure Strength	Force of 2kg is applied to each lead in axial direction for $10\text{s} \pm 1\text{s}$ (see drawing). No visible damage and it shall fulfill the specifications in Fig 1	Mechanical damage such as breaks shall not occur.

Email: info@global-antenna.com Tel: 86-371-58561629

Add: Room 1124,BLDG C,Chaoliumao,High-Tech Zone, Zhengzhou,China

GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

<https://www.global-antenna.com>

FIG 1




TABLE 1


Item	Specification After Test (MHz)
Center Frequency change	± 2.0

7. PACKAGE

To protect the products in storage and transportation, it is necessary to pack them (outer and inner package). On paper pack, the following requirements are requested.

7.1 Dimensions and Mark

At the end of package, the warning (moisture proof, upward put) should be stick to it. Dimensions and Mark (see below)



unit:mm

Email: info@global-antenna.com Tel: 86-371-58561629

Add: Room 1124,BLDG C,Chaoliumao,High-Tech Zone, Zhengzhou,China

GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

<https://www.global-antenna.com>

NO.	Name	Quantity
1	Inner Box	4
2	Package	1
3	Vacuum Bag	8
4	Certificate of approval	1
5	Label	9
6	Cushion	40
7	Package Base	48
8	Adhesive tape	3.5m


7.2 Section of package

Package is made of corrugated paper with thickness of 0.8cm. Package has 4 inner boxes, each box has 2 vacuum bag.

7.3 Quantity of package

Per package base 50 elements
Per vacuum bag 5 package bases
Per inner box 2 vacuum bag
Per package 4 inner boxes
(2000 pieces of elements)

7.4 Inner box Dimensions(unit:mm)



Email: info@global-antenna.com Tel: 86-371-58561629

Add: Room 1124,BLDG C,Chaoliumao,High-Tech Zone, Zhengzhou,China

GLOBAL EAST ASIA TECHNOLOGY CO.,LTD

<https://www.global-antenna.com>

8. OTHER

8.1 Caution of use

8.1.1 Please don't apply excess mechanical stress to the component and terminals at soldering.

8.1.2 The component may be damaged when an excess stress will be applied.

8.1.3 This specification mentions the quality of the component as a single unit. Please insure the component is thoroughly evaluated in your application circuit.

8.2 Notice

8.2.1 Please return one of these specifications after your signature of acceptance.

8.2.2 When something gets doubtful with this specification, we shall jointly work to get an agreement

Email: info@global-antenna.com Tel: 86-371-58561629

Add: Room 1124,BLDG C,Chaoliumao,High-Tech Zone, Zhengzhou,China