

AN3216 Series

Multilayer Chip Antenna

Features

- ❖ Monolithic SMD with small, low-profile and light-weight type.
- ❖ Wide bandwidth
- ❖ RoHS compliant



Applications

- ❖ Bluetooth/Wireless LAN/Home RF
- ❖ ISM band 2.4GHz applications

Specifications

Part Number	Operating Frequency (MHz)	Peak Gain (XZ-V)	Average Gain (XZ-V)	VSWR	Impedance
AN3216	2400 ~ 2500	0.5 dBi typ.	-0.5 dBi typ.	2 max.	50 Ω

Q'ty/Reel (pcs) : 3,000pcs
Operating Temperature Range : -40 ~ +85 °C
Storage Temperature Range : +5 ~ +35 °C, Humidity 45~75%RH
Storage Period : 12 months max.
Power Capacity : 2W max.

Part Number


AN 3216

① ②

Material Code

Identifier		Frequency Range	2450MHz
① Type	AN : Antenna	② Dimensions (L × W)	3.2× 1.6 mm
Material Code+BW	100MHz	Packaging	R: Tape & Reel B: Bulk


Terminal Configuration



No.	Terminal Name	No.	Terminal Name
①	Feeding Point	②	NC


Dimensions and Recommended PC Board Pattern

Unit : mm




Mark	L	W	T	a
Dimensions	3.2±0.2	1.6±0.2	1.3+0.1/-0.2	0.5±0.3

(a) Without Matching Circuits




(b) With Matching Circuits



*Line width should be designed to match 50Ω characteristic impedance, depending on PCB material and thickness.

Typical Electrical Characteristics (T=25°C)





❖ Test Board




❖ Return Loss

(a) Without Matching Circuits



(b) With Matching Circuits





Radiation Patterns




XZ cut @2.45GHz
 — Vertical
 Horizontal



YZ cut @2.45GHz
 — Vertical
 Horizontal




XY cut @2.45GHz
 — Vertical
 Horizontal




Taping Specifications

❖Tape & Reel Dimensions (Unit: mm) vs. Quantity (pcs)




Type	A	A'	B	C	D	E	F	T	Quantity/per reel	Tape material
AN3216	4.0±0.1	4.0±0.05	1.95±0.1	3.5±0.1	2.0±0.05	3.5±0.05	8.00±0.2	1.50±0.1	3,000pcs	Plastic (Embossed)

❖Reel Dimensions (Unit: mm)




Type	W2	W3	W4	W5
AN3216	178±1	60±1	1.4±0.2	17±0.5

❖Leader and Trailer Tape



❖Peel-off Force



Peel-off force should be in the range of 0.1 – 0.6 N at a peel-off speed of 300 ± 10 mm/min .


❖Storage Conditions

- (1) Temperature: $15\sim35^{\circ}\text{C}$, relative humidity (RH): 45~75%.
- (2) Non-corrosive environment

Notes

❖The contents of this data sheet are subject to change without notice. Please confirm the specifications and delivery conditions when placing your order.


Mechanical & Environmental Characteristics

Item	Requirements	Procedure
Solderability	- No apparent damage - More than 95% of the terminal electrode shall be covered with new solder	- Preheat: $120 \pm 5^{\circ}\text{C}$ - Solder: $245 \pm 5^{\circ}\text{C}$ for 5 ± 1 sec
Soldering strength (Termination Adhesion)	1kg minimum	- Solder specimen onto test jig. - Apply push force at 0.5mm/s until electrode pads are peeled off or ceramic are broken. Pushing force is applied to longitude direction
Deflection (Substrate Bending)	No apparent damage	- Solder specimen onto test jig (FR4, 0.8mm) using the recommend soldering profile. - Apply a bending force of 2mm deflection 
Heat/Humidity Resistance	- No apparent damage - Fulfill the electrical specification after test	- Temperature: $85 \pm 2^{\circ}\text{C}$ - Humidity: 90% ~ 95% RH - Duration: 1000 ± 48hrs - Recovery: 1-2hrs
Thermal shock (Temperature Cycle)	- No apparent damage - Fulfill the electrical specification after test	- One cycle/step 1 : $125 \pm 5^{\circ}\text{C}$ for 30 min step 2 : $-40 \pm 5^{\circ}\text{C}$ for 30 min - No of cycles : 100 - Recovery: 1-2 hrs
Low Temperature Resistance	- No apparent damage - Fulfill the electrical specification after test	- Temperature: $-40^{\circ} \pm 5^{\circ}\text{C}$ - Duration: 500 ± 24hrs - Recovery: 1-2hrs

Soldering Conditions

❖ Typical Soldering Profile for Lead-free Process

Reflow Soldering :



Notes

❖ The contents of this data sheet are subject to change without notice. Please confirm the specifications and delivery conditions when placing your order.